

MUZZLELOADER ROUND BALL DOUBLE CAVITY MOLDS - 0.600"

ROUND BALL 324.25GR ROUND DOUBLE CAVITY MOLD

The Lee Round Ball Moulds have a tangential cut off which eliminates the objectional nib at the sprue. Handles and Sprue plate included.



Attributes

- Name: 0.600" ROUND BALL 324.25GR ROUND DOUBLE CAVITY MOLD
- Manufacturer: LEE PRECISION
- Product no.: 100032183
- Mfr. No.: 90975
- Bullet Style: -
- Bullet Weight (Grains): -
- Cavities: -
- Diameter (in): -
- Delivery weight: 0.431kg
- Shipping height: 51mm
- Shipping width: 864mm
- Shipping length: 279mm
- UPC: 734307909758

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [English: Safety Instruction Guide for MUZZLELOADER ROUND BALL DOUBLE CAVITY MOLDS 0.600" ROUND BALL 324.25GR ROUND DOUBLE CAVITY MOLD](#)

Safety Instruction Guide for MUZZLELOADER ROUND BALL DOUBLE CAVITY MOLDS 0.600" ROUND BALL 324.25GR ROUND DOUBLE CAVITY MOLD

Introduction

Thank you for choosing the MUZZLELOADER ROUND BALL DOUBLE CAVITY MOLDS. This guide provides essential safety instructions and usage guidelines to ensure your safe experience with the product. Please read this document carefully before use.

General Safety Guidelines

- Always use the product in accordance with the manufacturer's instructions.
- Keep out of reach of children and vulnerable individuals.
- Inspect the product for any damage before use. Do not use if damaged.
- Store the product in a cool, dry place away from direct sunlight.
- Report any unsafe products or accidents to the appropriate authorities.
- Check for recall updates on the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Wear appropriate personal protective equipment (PPE), such as safety goggles and gloves, when handling the mold.
- Ensure the working area is wellventilated to avoid inhalation of fumes during use.
- Use caution when handling hot materials to prevent burns.
- Avoid contact with sharp edges of the mold to prevent cuts.
- Do not exceed the recommended temperature limits while using the mold.
- Ensure that the mold is securely clamped to a stable work surface before use.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary materials and tools before starting the process.
- Ensure the mold is clean and free of debris.

2. Installation:

- Secure the mold to a stable work surface using clamps.
- Check that the sprue plate is properly aligned and tightened.

3. Usage:

- Preheat the mold according to the manufacturer's guidelines.
- Pour the molten lead into the cavity of the mold carefully to avoid spills.
- Allow the lead to cool and solidify before opening the mold.
- Use the tangential cutoff feature to eliminate any nibs at the sprue.
- After use, clean the mold thoroughly and store it properly.

Disposal Instructions

- Dispose of any waste materials in accordance with local regulations.
- Do not dispose of lead waste in regular trash; follow hazardous waste disposal guidelines.

Contact Information for Further Support

For any safety inquiries or further assistance, please consult your local distributor or the manufacturer's customer service.

Thank you for your attention to these safety instructions. Your safety is our priority.