

1A2-25C BIPOD SLING SWIVEL MOUNT - HARRIS 1A2-25C BIPOD SLING SWIVEL MOUNT 13-27" BLACK

[Shooting Accessories](#) > [Bipods, Monopods & Accessories](#) > [Bipods](#)

Mounts to QD swivel studs on bolt action and single-shot rifles for ultimate field accuracy. Won't change zero; added weight steadies gun. Spring-loaded, telescoping legs adjust quickly, fold parallel to barrel for carrying. Series 1A2 bipods have solid base and do not swivel or rotate. Series S bipods rotate 45° for instant leveling on uneven ground. Buffer springs and adjustable tension on hinged base help eliminate tremor. All Models available in either Series. All Adapters fit either Series bipods. Not recommended for lever actions.



Attributes

- Name: [HARRIS 1A2-25C BIPOD SLING SWIVEL MOUNT 13-27" BLACK](#)
- Manufacturer: [HARRIS](#)
- Product no.: 416025227
- Mfr. No.: 1A2-25C
- Colour: Black
- Feet Material: Rubber
- Folding: Yes
- Height: 13 to 27
- Style: Cant Swivel
- Delivery weight: 0.499kg
- Shipping height: 43mm
- Shipping width: 97mm
- Shipping length: 422mm
- UPC: 051156112277

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for 1A225C BIPOD SLING SWIVEL MOUNT
- About Us

Safety Instruction Guide for 1A225C BIPOD SLING SWIVEL MOUNT

Introduction

Thank you for choosing the 1A225C Bipod Sling Swivel Mount by Harris. This product is designed to enhance your shooting accuracy while ensuring safety during use. Please read this safety instruction guide carefully to ensure proper use and maintenance of the bipod mount.

General Safety Guidelines

- Always ensure the bipod is securely mounted before use.
- Do not exceed the recommended height range of 13 to 27 inches.
- Regularly inspect the bipod for any signs of wear or damage before each use.
- Keep the bipod out of reach of children and vulnerable individuals.
- Report any unsafe conditions or accidents to the relevant authorities.

Specific Safety Precautions for Use

- Ensure that the bipod is attached to a compatible QD swivel stud.
- Avoid using the bipod on unstable or uneven surfaces without proper stabilization.
- Do not use the bipod for lever action rifles, as it is not recommended for this type of firearm.
- When adjusting the height, do so slowly and carefully to avoid pinching fingers.
- Always check that the legs are fully extended and locked before use.

Instructions for Installation and Usage

1. Installation:

- Locate the QD swivel stud on your rifle.
- Align the bipod mount with the swivel stud and secure it firmly.
- Ensure that the bipod is stable and does not wobble.

2. Adjusting Height:

- To adjust the height, pull the springloaded legs downward to the desired height.
- Make sure to lock the legs in place after adjustment to prevent accidental collapse.

3. Folding for Carrying:

- To fold the bipod for easy carrying, pull the legs parallel to the barrel.
- Ensure that the legs are securely folded and will not extend during transport.

4. Maintenance:

- Regularly clean the bipod with a soft cloth to remove dirt and debris.
- Inspect the rubber feet for wear and replace if necessary to maintain stability.

Disposal Instructions

- Dispose of the bipod in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Consider recycling materials where possible.

Contact Information for Further Support

For any questions or concerns regarding the product, please contact your local retailer or authorized service center. Ensure you have your product information available for reference.

Thank you for your attention to these safety instructions. Enjoy using your 1A225C Bipod Sling Swivel Mount responsibly!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk