

# PC-4 BIPODS - ACCU-TAC PC-4 BIPOD QUICK DETACH FOR PICATINNY RAIL MATTE BLACK

[Shooting Accessories](#) > [Bipods, Monopods & Accessories](#) > [Bipods](#)

**ACCU-TAC PC-4 BIPODS** The Accu-Tac PC-4 bipod was designed, engineered, and manufactured in the USA. This PC bipod is perfect for tactical, target, competition, and airgun shooting. This is only a suggested use, this model is not exclusive for these applications. The PC-4 is 100% billet, made from the highest quality aircraft aluminum available. This model has the versatility you want in a bipod with its 4 individual leg positions and 5 notch height options. It also has the ability to pan as well as cant, which can each be locked and secured individually with the adjustable lever. To engage or adjust leg position, simply pull the spring-loaded leg downward to move each leg independently. Leg position can be deployed to 90° or 45°, locking securely into 4 positions. Please keep in mind the cant adjustment lever can be repositioned, DO NOT use a tool to tighten the canting tension. All are black with anodized finish. Choose: Model PCB-0400 Quick Detach for Picatinny rail mount that is quick, and very secure, it attaches to a 1913 Picatinny rail and mounts in seconds without need for extra tools for tightening. Model PCASQD-0400 Quick Detach for Arca Swiss or Arca Style rail, mounts in seconds without the need to use extra tools for tightening. Model PCB-0400 QD for Picatinny Rail Specs Min. Height (Legs at 45°) 6.25"" / 158.75 mm Min. Height (Legs at 90°) 7.75"" / 196.85 mm Max. Height (Legs at 90°) 9.125" / 231.775 mm Min. Stance (Legs at 45°) 9.0" / 228.6 mm Max. Stance (Legs at 90°) 11.0"" / 279.4 mm Closed Position Width 4.250"" / 107.95 mm Closed Position Length 7.5" / 190.5 mm Weight 26.96 oz Model PCASQD-0400 Arca Spec Quick Detach Specs Min. Height (Legs at 45°) 6.50"" / 165.10 mm Min. Height (Legs at 90°) 8.00"" / 203.2 mm Max. Height (Legs at 90°) 9.150" / 232.41 mm Min. Stance (Legs at 45°) 9.0" / 228.6 mm Max. Stance (Legs at 90°) 11.0"" / 279.4 mm Closed Position Width 4.250"" / 107.95 mm Closed Position Length 7.5" / 190.5 mm Weight 27.92 oz"



## Attributes

- Name: [ACCU-TAC PC-4 BIPOD QUICK DETACH FOR PICATINNY RAIL MATTE BLACK](#)
- Manufacturer: [ACCU-TAC](#)
- Product no.: 430105234
- Mfr. No.: PCB-0400
- Attachment: Picatinny
- Colour: Black
- Feet Material: Aluminum
- Height: 2.56
- Weight: 1.88 lbs
- Delivery weight: 2.268kg
- Shipping height: 127mm
- Shipping width: 267mm
- Shipping length: 330mm
- UPC: 858520006343

## Item details

Made in USA

# Table of Contents

- Startpage
- Safety Instruction Guide for ACCUTAC PC4 Bipods
- About Us

# Safety Instruction Guide for ACCUTAC PC4 Bipods

## Introduction

Thank you for choosing the ACCUTAC PC4 Bipod. This guide provides essential safety instructions and information to ensure the safe and effective use of your bipod. Please read this guide carefully before using the product.

## General Safety Guidelines

- Ensure that the bipod is used only for its intended purposes, such as tactical, target, competition, and airgun shooting.
- Always inspect the bipod before each use for any signs of damage or wear.
- Ensure that the bipod is securely attached to the firearm or other equipment before use.
- Do not exceed the maximum weight limit of the bipod.
- Keep the bipod out of reach of children and unauthorized users.
- Always follow local laws and regulations regarding firearm accessories and usage.

## Specific Safety Precautions for Use

- When adjusting leg positions, ensure that your fingers are clear of any moving parts to avoid pinching or injury.
- Do not use excessive force when adjusting the cant and pan mechanisms; always use the adjustable lever provided.
- Ensure that the cant adjustment lever is not tightened with a tool; this may cause damage or malfunction.
- Be cautious of the bipod's stability, especially on uneven surfaces, to prevent tipping.
- Avoid using the bipod in extreme weather conditions that may affect its performance or safety.

## Instructions for Installation and Usage

### Installation

#### 1. Select the Appropriate Mounting Model:

- Model PCB0400 for Picatinny rail.
- Model PCASQD0400 for Arca Swiss or Arca Style rail.

#### 2. Attach the Bipod:

- Align the bipod with the rail mount.
- Slide the bipod onto the rail until it clicks into place.
- Ensure that the bipod is securely attached by pulling gently on it.

#### 3. Adjust the Legs:

- Pull the springloaded leg downward to adjust the leg position.
- Deploy the legs to either 90° or 45° angles.
- Ensure that the legs lock securely into one of the four available positions.

### Usage

- To adjust the height, pull the springloaded leg and set it to the desired notch height.
- For panning, loosen the pan adjustment lever and move the bipod side to side as needed.
- For canting, loosen the cant adjustment lever to tilt the bipod forward or backward, then tighten to

secure.

## **Maintenance**

- Regularly clean the bipod with a soft cloth to remove dirt and debris.
- Inspect the bipod for any signs of wear or damage after each use, especially the leg mechanisms and attachment points.

## **Disposal Instructions**

- Dispose of the bipod in accordance with local regulations.
- If the bipod is damaged beyond repair, recycle materials where possible, and ensure that any hazardous materials are disposed of safely.

## **Contact Information for Further Support**

For any safety inquiries or support regarding your ACCUTAC PC4 Bipod, please contact the manufacturer or your local distributor. Ensure you have your product details ready for a quicker response.

By following these safety instructions, you can enjoy the full benefits of your ACCUTAC PC4 Bipod while ensuring a safe shooting experience. Thank you for prioritizing safety!

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)