

GAS BLOCK FRONT SIGHT RUGER® AC-556 STYLE - SAMSON MANUFACTURING CORP GAS BLOCK AC-556 STYLE FRONT SIGHT 2008/LATER BLACK

[Rifle Parts](#) > [Gas System Parts](#) > [Gas Blocks](#)

Samson Mfg's reengineered version of the original AC-556 style gas block front sight with integrated sling attachment point. 2008 or later in Black or Stainless are compatible with Mini-14® rifles with a factory flanged .625" diameter barrel manufactured in 2008 or later, with a serial number prefix of 508 or higher. Additionally, Mini Thirty® rifles with the older factory straight pencil .625" diameter barrel and the new factory flanged .625" diameter barrel will be compatible. 2007 or earlier in Black or Stainless are compatible with Mini-14® rifles with a factory straight pencil .562" diameter barrel manufactured in 2007 or earlier, with a serial number prefix of 181 through 199, but not including 580 or higher.



Samson Mfg's reengineered version of the original AC-556 style gas block front sight with integrated sling attachment point. 2008 or later in Black or Stainless are compatible with Mini-14® rifles with a factory flanged .625" diameter barrel manufactured in 2008 or later, with a serial number prefix of 508 or higher. Additionally, Mini Thirty® rifles with the older factory straight pencil .625" diameter barrel and the new factory flanged .625" diameter barrel will be compatible. 2007 or earlier in Black or Stainless are compatible with Mini-14® rifles with a factory straight pencil .562" diameter barrel manufactured in 2007 or earlier, with a serial number prefix of 181 through 199, but not including 580 or higher.

Attributes

- Name: [SAMSON MANUFACTURING CORP GAS BLOCK AC-556 STYLE FRONT SIGHT 2008/LATER BLACK](#)
- Manufacturer: [SAMSON MANUFACTURING CORP](#)
- Product no.: 430107469
- Mfr. No.: 02-00068-03
- Inside Diameter: .625
- Material: Stainless Steel
- Style: Screw
- Weapon type: AR-15
- Delivery weight: 0.113kg
- Shipping height: 38mm
- Shipping width: 137mm
- Shipping length: 121mm
- UPC: 850028390566

Item details

Made in USA

US export classification: 0A501.x

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for GAS BLOCK FRONT SIGHT RUGER® AC556 STYLE](#)
- [About Us](#)

Safety Instruction Guide for GAS BLOCK FRONT SIGHT RUGER® AC556 STYLE

Introduction

Thank you for choosing the GAS BLOCK FRONT SIGHT RUGER® AC556 STYLE by SAMSON MANUFACTURING CORP. This guide provides essential safety information and instructions for the proper use and installation of your product. Please read this guide carefully to ensure safe and effective operation.

General Safety Guidelines

- Always use the product in accordance with the manufacturer's instructions.
- Inspect the product before each use for any signs of wear or damage.
- Ensure the product is compatible with your firearm model before installation.
- Keep this product out of reach of children and unauthorized users.
- If you experience any issues or suspect a defect, discontinue use immediately and consult a qualified gunsmith.
- Report any unsafe products or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Ensure that the firearm is unloaded before attempting to install or adjust the gas block front sight.
- Use only compatible Mini14® and Mini Thirty® rifles as specified in the product description.
- Avoid using the product in adverse conditions that may affect its performance, such as extreme temperatures or moisture.
- Always wear appropriate eye and ear protection when handling firearms.
- Do not modify or alter the gas block front sight in any way, as this may compromise its safety and effectiveness.

Instructions for Installation and Usage

1. Preparation

- Ensure your firearm is unloaded and in a safe condition.
- Gather necessary tools for installation, such as a wrench and screwdriver.

2. Installation Steps

- Remove the existing gas block front sight from your firearm if applicable.
- Align the new gas block front sight with the barrel, ensuring it fits securely.
- Tighten the screws using the appropriate tools, ensuring a snug fit without overtightening.
- Recheck alignment and stability of the gas block front sight.

3. Usage

- After installation, conduct a function check to ensure the gas block front sight is properly installed and aligned.
- Regularly inspect the gas block front sight for any signs of wear or loosening during routine maintenance.

Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- If the product becomes damaged or is no longer usable, dispose of it responsibly. Consider recycling materials where possible.

Contact Information for Further Support

For any inquiries or further assistance regarding safety concerns or product information, please refer to the manufacturer's contact details provided with your purchase.

Thank you for your attention to these safety guidelines. Your safety and satisfaction are our top priorities. Always prioritize safe handling and maintenance of your firearm and its components.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk