

TALL SERRATED SIGHT SETS FOR GLOCK® - BROWNELLS XL-TALL BLACK SIGHT SET SERRATED .315" F/.394" R FOR GLOCK

[Handgun Parts](#) > [Sights](#) > [Sight Sets](#)

Brownells Tall Sight Sets for Glock® These Tall Sight Sets are intended for use with Brownells slides, but will work perfect on any standard Glock® firearm with standard sight Glock® cuts. Front serrated sights are finished matte black to reduce glare. The rear sights are also serrated, and feature a U-Notch rear cut, making placement of the front sight in the notch quick and intuitive. Various heights allow you to optimize your sight set with your preferred red dot. Model Selection: 1L - Glock® 43x/48 with Holosun® 507k/407k, EPS Carry or Vortex® Defender- Slimmer width rear sight but still fits 17/19 width rear sight cut. With Holosun EPS on a standard Glock MOS this will result in a lower 1/3 co-witness. XL - Glock® Gen 3/4/5 with Aimpoint® Acro®, Holosun 509T or Steiner® MPS 3XL - Glock® Gen 3/4/5 with Holosun 407C/507C/508T, Trijicon® RMR®/RMR HD®/RCR®/SRO® or EOTech® EFLX Heights: 1L - .220" Front / .295" Rear XL - .315" Front / .394" Rear 3XL - .365" Front / .451" Rear DISCLAIMER: "GLOCK" is a federally registered trademark of GLOCK, Inc. and is one of many trademarks owned by GLOCK, Inc. or GLOCK Ges.m.b.H. Neither Brownells nor this site are affiliated in any manner with, or otherwise endorsed by, GLOCK, Inc. or GLOCK Ges.m.b.H. The use of "GLOCK" on this page is merely to advertise the sale of GLOCK pistols, parts, or components. For genuine GLOCK, Inc. and GLOCK Ges.m.b.H. products and parts visit www.glock.com.



Attributes

- Name: [BROWNELLS XL-TALL BLACK SIGHT SET SERRATED .315" F/.394" R FOR GLOCK](#)
- Manufacturer: [BROWNELLS](#)
- Product no.: 430110328
- Mfr. No.: GL-855
- Sight Color: Black
- Style: U Notch
- Weapon type: Glock
- Delivery weight: 0.526kg
- Shipping height: 178mm
- Shipping width: 24mm
- Shipping length: 140mm
- UPC: 644406914273

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for TALL SERRATED SIGHT SETS FOR GLOCK® BROWNEULLS XLTALL BLACK SIGHT SET
- About Us

Safety Instruction Guide for TALL SERRATED SIGHT SETS FOR GLOCK® BROWNELLS XLTALL BLACK SIGHT SET

Introduction

Thank you for purchasing the TALL SERRATED SIGHT SETS FOR GLOCK® by Brownells. Your safety is our priority, and we want to ensure that you can use this product effectively and safely. This guide provides essential safety instructions, installation guidelines, and contact information for further support.

General Safety Guidelines

- Always ensure that your firearm is unloaded and pointed in a safe direction before installing or adjusting the sights.
- Inspect the sight set for any visible damage before use. Do not use if damaged.
- Follow all local laws and regulations regarding firearm modifications and usage.
- Keep the sight set out of reach of children and unauthorized users.
- Use protective eyewear when installing or handling the sight set to avoid injury.
- Report any unsafe products or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- Ensure that the sight set is compatible with your specific model of Glock® before installation.
- When using the sights, be aware of your surroundings and ensure a safe shooting environment.
- Avoid using the sight set in adverse weather conditions that may impair visibility.
- Regularly check the sight set for tightness and alignment to ensure it remains securely attached.
- If you experience any issues with the sight set during use, cease operation immediately and inspect for problems.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including a screwdriver and any specific tools recommended for your Glock® model.
- Ensure your firearm is completely unloaded and safe to handle.

2. Removing the Old Sights:

- Use the appropriate tool to remove the existing sights from your Glock®.
- Keep the screws and components in a safe place for potential future use.

3. Installing the New Sights:

- Align the front sight with the designated cut on the slide.
- Secure the front sight using the provided screws, ensuring it is tight but not overtorqued.
- Align the rear sight in the same manner, ensuring it fits securely in the rear sight cut.
- Doublecheck that both sights are aligned properly for optimal accuracy.

4. Final Checks:

- Ensure all screws are tightened and the sights are secure.

- Perform a function check to confirm that the sights are properly aligned and operational.
- If applicable, adjust the sights according to your shooting preferences.

5. Usage:

- Practice using the new sights in a safe and controlled environment.
- Familiarize yourself with the sight picture and alignment for effective shooting.

Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- If the sight set is no longer usable, dispose of it responsibly, ensuring that it does not pose a safety hazard to others.
- Recycle materials where possible.

Contact Information for Further Support

For any inquiries related to safety, installation, or product issues, please refer to the manufacturer's website or contact their customer service department directly.

By following these safety guidelines, you can ensure a safe and effective experience with your TALL SERRATED SIGHT SETS FOR GLOCK®. Thank you for choosing Brownells, and please shoot safely!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk