

HIGH TEMP CERAMIC THREADLOCKER - BROWNEILLS THREADLOCKER, CERAMIC HIGH TEMP, 2OZ BOTTLE

[Gunsmith Tools](#) > [General Gunsmith Tools](#) > [Thread Locking Liquids](#)

HIGH TEMP CERAMIC THREADLOCKER The Brownells High Temp Ceramic Threadlocker is a specialized adhesive formulated to secure threaded fasteners exposed to extreme temperatures, accommodating a range from -60°F to 2000°F (-51°C to 1000°C). Key Features: Ceramic Formulation: Provides exceptional thermal stability, maintaining bond integrity under extreme heat conditions. Water-Based Cure: Cures through the evaporation of water, with exposure to temperatures over 230°F (110°C) accelerating fixture time. Extended Shelf Life: Offers up to a 24-month shelf life once opened, ensuring long-term usability. Specifications: Fixture Time: 2-6 hours at 72°F (22°C). Full Cure Time: 24 hours at 72°F (22°C). Temperature Range: -60° F to 2000° F / -51° C to 1000° C Container Size: 1.8ml Tube or 2 oz Bottle.

Application Instructions: Surface Preparation: Ensure parts are clean, dry, and free from oil or grease. Application: Apply the threadlocker to the threads, covering a length approximately 1.5 times the diameter of the part. Curing: Allow the coated parts to dry for 2-6 hours at 72°F (22°C). Exposure to temperatures over 230°F (110°C) will accelerate fixture time. Instructions for Use: Parts must be clean, dry and free from oil or grease. Brownells High Temp Ceramic Threadlocker cures through evaporation of water in order to build strength. Exposure to temperatures over 230° F (110°C) accelerates fixture time. Incorporating the Brownells High Temp Ceramic Threadlocker into your assembly process ensures that threaded components remain secure under extreme temperature conditions, enhancing the reliability and safety of your equipment.



Attributes

- Name: [BROWNEILLS THREADLOCKER, CERAMIC HIGH TEMP, 2OZ BOTTLE](#)
- Manufacturer: [BROWNEILLS](#)
- Product no.: 430110334
- Mfr. No.: 19960BROWN
- Colour: Clear
- Size: 2 oz
- Delivery weight: 0.045kg
- Shipping height: 124mm
- Shipping width: 48mm
- Shipping length: 118mm
- UPC: 050806001312

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for Brownells High Temp Ceramic Threadlocker
- About Us

Safety Instruction Guide for Brownells High Temp Ceramic Threadlocker

Introduction

Thank you for choosing Brownells High Temp Ceramic Threadlocker. This specialized adhesive is designed to securely bond threaded fasteners exposed to extreme temperatures. Please read this safety instruction guide carefully to ensure safe and effective use of the product.

General Safety Guidelines

- Always store the product in a cool, dry place away from direct sunlight and heat sources.
- Keep the product out of reach of children and pets.
- Use the product only as intended and according to the instructions provided.
- If you experience any adverse reactions, stop use immediately and seek medical attention.
- Report any unsafe products or incidents to the relevant authorities.
- Regularly check for updates on product recalls via the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Personal Protective Equipment (PPE):**
 - Wear gloves and safety goggles when handling the product to prevent skin and eye contact.
- **Ventilation:**
 - Ensure adequate ventilation in the area where the product is used to avoid inhalation of vapors.
- **Avoid Ingestion:**
 - Do not ingest the product. If swallowed, seek medical assistance immediately.
- **Skin Contact:**
 - In case of skin contact, wash the affected area thoroughly with soap and water.
- **Eye Contact:**
 - In case of contact with eyes, rinse immediately with plenty of water and seek medical attention.

Instructions for Installation and Usage

1. Surface Preparation:

- Ensure that all parts to be bonded are clean, dry, and free from oil or grease.

2. Application:

- Apply the threadlocker to the threads, covering a length approximately 1.5 times the diameter of the part.

3. Curing:

- Allow the coated parts to dry for 26 hours at 72°F (22°C).
- Exposure to temperatures over 230°F (110°C) will accelerate fixture time.

4. Storage After Use:

- After application, ensure the cap is tightly closed to maintain product integrity.
- Store the product in its original container in a cool, dry place.

Disposal Instructions

- Dispose of any unused product or empty containers in accordance with local regulations.
- Do not dispose of the product in household waste. Check for local disposal options for hazardous materials.

Contact Information for Further Support

For any questions or concerns regarding the use of Brownells High Temp Ceramic Threadlocker, please refer to the product packaging or visit the manufacturer's website for additional resources.

Thank you for your attention to these safety instructions. Your safety and the effective use of this product are our top priorities.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk