## **SEMI-AUTO SAFETY SELECTOR**

SEMI-AUTO SAFETY SELECTOR Semi-Auto Ambidextrous Safety Selector. This no frills, tough as nails, ambi safety is a perfect low cost upgrade to your LMT or any other AR-15/AR-10 weapon system. This is a steel, two piece design with equal length levers for quick and effective engagement of the safety in practical usage. Builders will need the safety detent and spring. Also Available in right hand only.



## **Attributes**

• Name: SEMI-AUTO SAFETY SELECTOR

Manufacturer: LMT DEFENSEProduct no.: 430111547Mfr. No.: LMP092A

Delivery weight: 0.018kgUPC: 815415017143

• Make: AR-15

#### Item details

Made in USA

US export classification: 0A501.x

# **Table of Contents**

- StartpageEnglish: SEMIAUTO SAFETY SELECTOR Safety Instruction Guide

# SEMIAUTO SAFETY SELECTOR Safety Instruction Guide

## Introduction

Thank you for choosing the SEMIAUTO SAFETY SELECTOR. This product is designed to enhance the safety and functionality of your AR15 or AR10 weapon system. It is important to follow all safety instructions and guidelines to ensure proper use and maintenance of this product. This guide provides essential safety information, installation instructions, and contact information for further support.

## **General Safety Guidelines**

- Ensure that the SEMIAUTO SAFETY SELECTOR is installed correctly to avoid any accidental discharges.
- Always treat your firearm as if it is loaded, even if you believe it is not.
- Keep the firearm pointed in a safe direction at all times.
- Store your firearm and safety selector in a secure location, away from children and unauthorized users.
- Regularly inspect the SEMIAUTO SAFETY SELECTOR for any signs of wear or damage.
- If you notice any defects or issues, discontinue use immediately and seek professional assistance.

## **Specific Safety Precautions for Use**

- Always engage the safety selector when the firearm is not in use.
- Be aware of your surroundings and ensure that you have a clear and safe shooting area.
- Do not modify the SEMIAUTO SAFETY SELECTOR or any part of your firearm in ways not recommended by the manufacturer.
- Use only compatible firearms as specified in the product description.
- Ensure that you have the necessary safety detent and spring for installation.

## Instructions for Installation and Usage

#### 1. Preparation:

- Ensure that the firearm is unloaded and pointed in a safe direction.
- Gather the necessary tools for installation, including a punch tool and a hammer.

#### 2. Installation Steps:

- Remove the existing safety selector from your firearm according to the manufacturer's instructions.
- Insert the new SEMIAUTO SAFETY SELECTOR into the designated slot on the lower receiver.
- Align the safety detent and spring as per the manufacturer's specifications.
- Use the punch tool to secure the safety selector in place, ensuring that it moves freely between the safe and fire positions.

#### 3. Usage:

- To engage the safety, push the lever to the "Safe" position.
- To disengage the safety, push the lever to the "Fire" position.
- Always ensure that the safety is engaged when the firearm is not in use or when handing it to another person.

## **Disposal Instructions**

- Dispose of the SEMIAUTO SAFETY SELECTOR and any associated materials in accordance with local regulations.
- Do not dispose of the product in regular household waste. Instead, check for local recycling or hazardous waste programs that accept metal components.

## **Contact Information for Further Support**

For any questions or concerns regarding the SEMIAUTO SAFETY SELECTOR, please refer to the manufacturer's customer service or support resources. Ensure that you have the product details available for efficient assistance.

By following these guidelines, you can ensure the safe and effective use of your SEMIAUTO SAFETY SELECTOR. Always prioritize safety and compliance with local laws and regulations when handling firearms.