

HELLFIRE TI SELF-TIMING MUZZLE BRAKE - HELLFIRE-TI 30 CAL SELF TIMING MUZZLE BRAKE GRAY TITANIUM

HELLFIRE TI SELF-TIMING MUZZLE BRAKE The Hellfire has transformed the muzzle brake industry. Unmatched versatility, modularity, ease of use, and performance. With the original 3-Port Hellfire now 8 years old, and the family having grown to include the Hellfire 2P, the Hellfire LFS, and the Hellfire Match, along with a serious family of suppressor mounts, there was always something Area 419 wanted to make. Now, it's time. This is the Hellfire Ti. CNC Milled right here in Ohio with a Grade 5 6Al-4V Titanium main body, the Hellfire Ti is built for your hunting rifle, with the performance you'd expect on your Match rifle. Features Available in 30, 40, and 50 cal variants, to accommodate common hunting cartridges up to and including 450 Bushmaster and 50 Beowulf Stainless Steel collar for greater mounting strength and durability 2.8oz in 30cal (brake body and collar) - 30% lighter than the Hellfire OG 1.1" port diameter (27% more braking surface than the Hellfire OG) Brake assembly will add 2.5" from the thread shoulder (approx 1.9" added to OAL of barrel) Gray Titanium anodize, reducing glare Flatter first port to reduce blast Progressive upper port geometry to control muzzle flip Patented Hellfire Mount system, for great versatility Caliber Selection For these brakes, caliber selection is simple. If your rifle is a 30-cal rifle (or smaller) you select the ".30 and Under" option. This includes 308, 300 RUM, 30-06. 300 Win Mag, etc - or ANYTHING smaller (7mm, 6.5mm, etc.). If your rifle is 40 cal or smaller (but larger than 30 cal) you should select the ".40 and Under" option. This would include 338s, 357/9mm, etc. If your rifle is 50 cal or smaller (but larger than 40 cal) you should select the ".50 and Under" option. This would include 458s, 45/70, etc. This brake IS NOT RATED FOR 50 BMG.



Attributes

- Name: HELLFIRE-TI 30 CAL SELF TIMING MUZZLE BRAKE GRAY TITANIUM
- Manufacturer: AREA 419
- Product no.: 430112720
- Mfr. No.: 419HFTI-300-5824
- Caliber: 30 Caliber (.308)
- Finish: Gray
- Material: Titanium
- Threads: -
- Delivery weight: 0.227kg
- Shipping height: 51mm
- Shipping width: 89mm
- Shipping length: 152mm
- UPC: 810080183384

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [English: HELLFIRE TI SELFTIMING MUZZLE BRAKE SAFETY INSTRUCTIONS](#)

HELLFIRE TI SELFTIMING MUZZLE BRAKE SAFETY INSTRUCTIONS

Introduction

Thank you for choosing the HELLFIRE TI SelfTiming Muzzle Brake. This product has been designed to enhance the performance of your hunting rifle while ensuring safety during use. Please read this safety instruction guide carefully to understand how to use, install, and dispose of the product safely.

General Safety Guidelines

- Ensure that the muzzle brake is compatible with your firearm before installation.
- Always handle firearms with care and follow local laws and regulations regarding firearm use.
- Keep the muzzle brake out of reach of children and unauthorized users.
- Regularly inspect the muzzle brake for any signs of wear or damage.
- Do not use this product with ammunition that exceeds the specified caliber limits.
- If you notice any unusual performance or sounds while using the muzzle brake, cease use immediately and consult a professional.

Specific Safety Precautions for Use

- Always wear appropriate eye and ear protection when using firearms equipped with a muzzle brake.
- Ensure that the firearm is unloaded before installing or removing the muzzle brake.
- Do not attempt to modify the muzzle brake in any way, as this may compromise safety and performance.
- Use only the recommended tools for installation and removal to avoid damage.
- Avoid pointing the firearm at anything other than your intended target.

Instructions for Installation and Usage

1. Installation:

- Ensure that the firearm is completely unloaded.
- Clean the muzzle of the barrel to remove any debris or residue.
- Align the muzzle brake with the threads of the barrel.
- Handtighten the muzzle brake onto the barrel, ensuring it is secure.
- Use a wrench to tighten the muzzle brake further, if necessary, but do not overtighten.
- Check that the muzzle brake is properly aligned and securely attached.

2. Usage:

- Before firing, ensure that the area is clear of obstructions and that you have a safe shooting backdrop.
- Fire the rifle as instructed, and monitor performance.
- After use, clean the muzzle brake according to the manufacturer's guidelines.

3. Removal:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Use the appropriate tools to carefully unscrew the muzzle brake from the barrel.
- Store the muzzle brake in a safe location when not in use.

Disposal Instructions

- Dispose of the muzzle brake in accordance with local regulations.
- If the product is damaged or no longer usable, contact your local waste management authority for proper disposal methods.
- Do not throw the product in regular household waste.

Contact Information for Further Support

For any inquiries regarding safety, installation, or performance of the HELLFIRE TI SelfTiming Muzzle Brake, please refer to the manufacturer's contact details provided with your product packaging.

Thank you for your attention to these safety instructions. Your safety and the safety of others is our top priority. Enjoy your experience with the HELLFIRE TI SelfTiming Muzzle Brake.