

HELLFIRE TI SELF-TIMING MUZZLE BRAKE - HELLFIRE-TI 50 CAL SELF TIMING MUZZLE BRAKE GRAY TITANIUM

HELLFIRE TI SELF-TIMING MUZZLE BRAKE The Hellfire has transformed the muzzle brake industry. Unmatched versatility, modularity, ease of use, and performance. With the original 3-Port Hellfire now 8 years old, and the family having grown to include the Hellfire 2P, the Hellfire LFS, and the Hellfire Match, along with a serious family of suppressor mounts, there was always something Area 419 wanted to make. Now, it's time. This is the Hellfire Ti. CNC Milled right here in Ohio with a Grade 5 6Al-4V Titanium main body, the Hellfire Ti is built for your hunting rifle, with the performance you'd expect on your Match rifle. Features Available in 30, 40, and 50 cal variants, to accommodate common hunting cartridges up to and including 450 Bushmaster and 50 Beowulf Stainless Steel collar for greater mounting strength and durability 2.8oz in 30cal (brake body and collar) - 30% lighter than the Hellfire OG 1.1" port diameter (27% more braking surface than the Hellfire OG) Brake assembly will add 2.5" from the thread shoulder (approx 1.9" added to OAL of barrel) Gray Titanium anodize, reducing glare Flatter first port to reduce blast Progressive upper port geometry to control muzzle flip Patented Hellfire Mount system, for great versatility Caliber Selection For these brakes, caliber selection is simple. If your rifle is a 30-cal rifle (or smaller) you select the ".30 and Under" option. This includes 308, 300 RUM, 30-06. 300 Win Mag, etc - or ANYTHING smaller (7mm, 6.5mm, etc.). If your rifle is 40 cal or smaller (but larger than 30 cal) you should select the ".40 and Under" option. This would include 338s, 357/9mm, etc. If your rifle is 50 cal or smaller (but larger than 40 cal) you should select the ".50 and Under" option. This would include 458s, 45/70, etc. This brake IS NOT RATED FOR 50 BMG.



Attributes

- Name: HELLFIRE-TI 50 CAL SELF TIMING MUZZLE BRAKE GRAY TITANIUM
- Manufacturer: AREA 419
- Product no.: 430112722
- Mfr. No.: 419HFTI-500-5824
- Caliber: 50 Caliber (.500-.501)
- Finish: Gray
- Material: Titanium
- Threads: NA
- Delivery weight: 0.227kg
- Shipping height: 51mm
- Shipping width: 89mm
- Shipping length: 152mm
- UPC: 810080183407

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [English: HELLFIRE TI SELFTIMING MUZZLE BRAKE Safety Instruction Guide](#)

HELLFIRE TI SELFTIMING MUZZLE BRAKE Safety Instruction Guide

Introduction

Thank you for choosing the HELLFIRE TI SelfTiming Muzzle Brake. This product is designed to enhance the performance of your hunting rifle while ensuring safe and effective use. Please read this safety instruction guide carefully to understand how to use the product safely and efficiently.

General Safety Guidelines

- Ensure that the muzzle brake is compatible with your firearm before use.
- Always handle firearms with care and follow standard safety protocols.
- Keep the muzzle brake out of reach of children and unauthorized users.
- Regularly inspect the muzzle brake for signs of wear or damage.
- Report any unsafe conditions or incidents related to this product to the relevant authorities.
- Stay informed about recalls or safety alerts by checking the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Only use the HELLFIRE TI Muzzle Brake with firearms that are rated for its caliber specifications.
- Do not use this muzzle brake with firearms chambered for 50 BMG, as it is not rated for this caliber.
- Ensure proper installation according to the provided instructions to avoid accidents or malfunctions.
- Always wear appropriate eye and ear protection when firing a weapon equipped with a muzzle brake.
- Be aware of your surroundings and ensure that the area is clear of bystanders when firing.

Instructions for Installation and Usage

Installation

1. **Preparation:** Ensure your firearm is unloaded and safe to handle.
2. **Threading:** Carefully thread the muzzle brake onto the barrel's threaded shoulder. Ensure that it is securely fastened.
3. **Alignment:** Align the brake so that the ports are positioned correctly for optimal performance.
4. **Tightening:** Use the appropriate tool to tighten the muzzle brake, ensuring a snug fit without overtightening.

Usage

- Before firing, doublecheck that the muzzle brake is properly installed and secure.
- When using the rifle, maintain a firm grip and proper stance to manage recoil effectively.
- After firing, inspect the muzzle brake for any signs of damage or loosening.
- Clean the muzzle brake regularly to maintain performance and prevent corrosion.

Disposal Instructions

When disposing of the HELLFIRE TI Muzzle Brake, follow these guidelines: * Dispose of the product in accordance with local regulations regarding metal waste. * Do not dispose of the product in regular household waste. * Contact local recycling centers for information on proper disposal methods for metal components.

Contact Information for Further Support

For any inquiries or concerns regarding the HELLFIRE TI SelfTiming Muzzle Brake, please refer to the contact

information provided on the packaging or product documentation.

By following these safety instructions, you can ensure a safe and enjoyable shooting experience with your HELLFIRE TI Muzzle Brake. Thank you for your commitment to safety.