

TACTICAL MID-CANTILEVERED 1-PIECE SCOPE MOUNTS - TACTICAL MID CANTILEVER 34MM DIA 34MM HEIGHT 0 MOA PIC MOUNT

TACTICAL MID CANTILEVERED 1-PIECE SCOPE MOUNTS When Area 419 set out to make the perfect scope mount, they knew what they needed to make something that was reliable and consistent at a degree you won't find anywhere else on the market. This led us down a rabbit-hole, ultimately arriving on a process that gets you final-bore matched rings, with raw aluminum internals, for a grip on your optic that is more reliable and more true than anything else made – as well as an incredible amount of robustness without adding unnecessary weight. Like most mounts, these begin as separate parts. Area 419 are making the bases and caps in batches. While many will make these parts, send them to anodize, and then just assemble, they produce around the extra steps. Once these parts return from anodize, they are fully assembled, placed back into specially produced rail fixtures, with the caps torqued to spec over specially made spacers (to give the rings space to torque down on the optic), and final-bored as sets in Area 419's world-class machining centers. Mounts are then brought off the machine in sets, QC'd and packaged, ensuring that you receive a mount that was finished perfectly. Is it overkill? Probably. But Area 419 think it's the right way. So that's what they are going to do. NOTE: All 1.34" (34mm) height mounts are a mid-cantilever, meant for less offset and use on bolt-action platforms. KEY FEATURES CNC Milled in America from American 7075 Aluminum Raw aluminum, precision bored scope contact surfaces for maximum grip Final-bored in sets, and never fully disassembled after boring 8-9oz per mount, depending on model, balancing weight management and robustness Multiple accessory mounting points Separate rail clamping bars for maximum grab on the pic rail Inset clamping feet, allowing for maximum mounting adjustment and pic rail utility Steel guide pins between base and caps, aiding in alignment Custom nitrided stainless hardware



Attributes

- Name: TACTICAL MID CANTILEVER 34MM DIA 34MM HEIGHT 0 MOA PIC MOUNT
- Manufacturer: AREA 419
- Product no.: 430112794
- Mfr. No.: 419-MCM-3434
- Elevation: 0 MOA
- Finish: Black
- Height: 5"
- Length: 2"
- Scope Tube Diameter: 34mm
- Style: Picatinny
- Delivery weight: 0.68kg
- Shipping height: 76mm
- Shipping width: 152mm
- Shipping length: 241mm
- UPC: 810080183230

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [English: TACTICAL MDCANTILEVERED 1PIECE SCOPE MOUNTS Safety Instruction Guide](#)

TACTICAL MIDCANTILEVERED 1PIECE SCOPE MOUNTS Safety Instruction Guide

Introduction

Thank you for choosing the TACTICAL MIDCANTILEVERED 1PIECE SCOPE MOUNTS by AREA 419. This guide provides essential safety instructions to ensure safe and effective use of your scope mount. Please read this guide thoroughly before installation and use.

General Safety Guidelines

- Ensure the product is used only for its intended purpose as a scope mount.
- Keep the product out of reach of children and vulnerable individuals to prevent accidents.
- Inspect the scope mount before each use for any signs of damage or wear.
- Report any unsafe products or accidents to the appropriate authorities.
- Stay updated on recall notices via the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Installation Safety:** Always ensure that the mount is securely attached to the firearm before use. Loose mounts can lead to misalignment and potential accidents.
- **Weight Management:** Be aware of the weight of the mount (89oz) and ensure that your firearm can accommodate this without affecting balance or handling.
- **Torque Specifications:** Follow the manufacturer's torque specifications during installation to prevent damage to the mount or firearm.
- **Clamping Mechanism:** Ensure that the inset clamping feet and rail clamping bars are properly adjusted for maximum grip and stability.
- **Material Safety:** The mount is made from CNC milled American 7075 Aluminum. Avoid exposure to extreme conditions that may compromise the integrity of the material.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including a torque wrench, to ensure proper installation.
- Ensure that the firearm is unloaded and pointed in a safe direction.

2. Mounting the Scope:

- Align the base of the scope mount with the picatinny rail on your firearm.
- Place the scope in the rings, ensuring proper eye relief and alignment.
- Use the clamping bars to secure the mount to the rail.

3. Torque Application:

- Using a torque wrench, apply the recommended torque to the clamping bars and caps. Refer to the specifications provided by AREA 419 for the correct torque values.

4. Final Inspection:

- After installation, doublecheck all connections and ensure that the mount is secure.
- Perform a visual inspection to confirm that there are no loose parts.

5. Usage:

- When using the firearm with the mounted scope, ensure that you maintain proper shooting posture and handling practices.
- Regularly check the mount for any signs of wear or loosening during use.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding metal and aluminum waste.
- Do not dispose of the product in household waste. Instead, seek out a recycling center that accepts aluminum products.

Contact Information for Further Support

For any questions or concerns regarding the TACTICAL MIDCANTILEVERED 1PIECE SCOPE MOUNTS, please refer to the manufacturer's website or contact your local dealer for assistance.

Thank you for your attention to these safety instructions. Your safety and satisfaction are our top priorities. Enjoy your new scope mount!