

MBUS PRO® HOODED FRONT SIGHT FOR AR-15 - MBUS PRO HOODED FRONT SIGHT FOR AR-15

MAGPUL® PRO HOODED FRONT SIGHT FOR AR-15 The MBUS (Magpul® Back-Up Sight) Pro Sight - Front, Hooded is an all-steel, back up front sight. The hooded front sight arm provides a profile that aids in faster sight acquisition while minimizing snagging. It's also just as durable as Magpul's other Pro sights thanks to a corrosion-resistant QPQ finish that delivers maximum functionality and strength with minimum bulk. When the Hooded Pro Front Sight is paired with the dual aperture, windage-adjustable MBUS Pro Sight - Rear, it can act as a diopter style sight (aperture within an aperture) depending on its placement in relation to the rear sight. Used with the MBUS Pro Sight - Rear, the toolless, elevation-adjustable MBUS Pro Sight set excels in all applications, including when mounted on rail-height gas blocks. Detents keep the Hooded Sight at standard AR sight-height when deployed, and it remains out of the way when it's stowed (measuring 1.71" from the sight base's leading edge to the top of the hood). Two front-post widths (.040" match or standard .060") are available to fit shooters' precision needs (the narrower width front is also compatible with most IR aiming laser and light installations for the professional user). Just like all Magpul's other sights, it's made in the USA.

FEATURES ALL STEEL CONSTRUCTION Finished with QPQ salt bath nitride for extreme resistance to wear and corrosion 0.432" HEIGHT ABOVE RAIL AT TALLEST POINT AND COVERS LESS THAN 1-3/4" OF RAIL WHEN STOWED STANDARD AR SIGHT HEIGHT WHEN DEPLOYED Positive detents in both the up and down positions as well as on the elevation knob Round hood protects sight post and acts as an 'aperture within an aperture' with a Rear MBUS Pro ELEVATION ADJUSTMENT KNOB Elevation adjustment knob - no tools required Steel, rectangular sight post selectable between Match and Standard widths: 0.04" Match width for increased precision 0.06" Standard width for maximum visibility SPECS Position: Front Height above rail, stowed: ~0.43 in. max Length, stowed: 1.7 in. Weight : 1.5 oz. Compatibility: Mounts on any MIL-STD-1913 Picatinny/STANAG 4694 rail including receiver-height gas blocks ELEVATION ADJUSTMENT ~1 MOA (1.131"/100 m) per click with a 14.5" sight radius ~0.7 MOA (0.820"/100 m) per click with a 20" sight radius



Attributes

- Name: MBUS PRO HOODED FRONT SIGHT FOR AR-15
- Manufacturer: MAGPUL
- Product no.: 430113698
- Mfr. No.: MAG1518-BLK
- Color: Black
- Make: AR-15
- Material: Steel
- Style: Folding
- Delivery weight: 0.036kg
- UPC: 840815149316

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [English: Safety Instruction Guide for MBUS PRO® HOODED FRONT SIGHT FOR AR15](#)

Safety Instruction Guide for MBUS PRO® HOODED FRONT SIGHT FOR AR15

Introduction

Thank you for choosing the MBUS PRO® Hooded Front Sight for your AR15. This product is designed for durability and precision. To ensure safe and effective use, please read and follow these safety instructions carefully.

General Safety Guidelines

- Ensure that the sight is installed correctly to avoid any accidents during use.
- Always handle firearms responsibly and in accordance with local laws and regulations.
- Regularly inspect the sight for any signs of wear or damage before use.
- Keep the product out of reach of children and unauthorized users.
- Report any unsafe conditions or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- Only use the MBUS PRO® Hooded Front Sight with compatible firearms as specified in the product documentation.
- Do not modify the sight in any way, as alterations may compromise safety and performance.
- Avoid using the sight in extreme environmental conditions that may affect its functionality.
- Ensure that the sight is properly stowed when not in use to prevent accidental deployment.
- Be aware of your surroundings and ensure a clear line of sight when aiming.

Instructions for Installation and Usage

1. Installation

- Ensure that the firearm is unloaded and safe before beginning installation.
- Locate the MILSTD1913 Picatinny rail on your AR15.
- Align the MBUS PRO® Hooded Front Sight with the rail, ensuring it sits securely.
- Use the provided mounting hardware to secure the sight in place. Tighten according to the manufacturer's specifications.
- Confirm that the sight is firmly attached and does not move when pulled or pushed.

2. Usage

- Adjust the elevation using the toolless elevation adjustment knob for optimal sight alignment.
- Utilize the positive detents to lock the sight in the up position when deployed.
- When not in use, stow the sight by pushing it down until it locks in the stowed position.
- For effective sight acquisition, practice aligning the front sight with the rear sight under various lighting conditions.

Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic and metal waste.
- Do not dispose of the sight in regular household waste.
- If the product is damaged or no longer functional, consult local waste management services for proper disposal methods.

Contact Information for Further Support

For any inquiries related to safety, installation, or product support, please consult the product packaging or official manufacturer website for the appropriate contact information.

By following these guidelines, you can ensure the safe and effective use of the MBUS PRO® Hooded Front Sight for your AR15. Thank you for prioritizing safety and responsible firearm use.