

# Compensator for 9mm Handgun - Primer Stop Switch for Dillon XL650

Take Full Control of Your Press: Primer Cam Index Stop Switch Streamline your reloading workflow on the Dillon Precision XL650 and SL-900. This innovative switch allows you to easily toggle the primer indexing system ON and OFF. By temporarily retracting the magnet-attached ramp, it allows the indexing lever to safely pass over the primer feed assembly without activating it—perfect for clearing jams, adjusting dies, or setting up cases without feeding primers.



## Attributes

- Name: Primer Stop Switch for Dillon XL650
- Manufacturer: ARMANOV
- Product no.: EU2018567
- Mfr. No.: PCSSD-US
- Colour: Black
- Delivery weight: 1kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 100mm

# Table of Contents

- [Startpage](#)
- [English: Compensator for 9mm Handgun Primer Stop Switch for Dillon XL650 Safety Instruction Guide](#)

# Compensator for 9mm Handgun Primer Stop Switch for Dillon XL650 Safety Instruction Guide

## Introduction

Thank you for choosing the Compensator for 9mm Handgun Primer Stop Switch for Dillon XL650. This innovative product is designed to enhance your reloading workflow and ensure a safer reloading experience. Please read this safety instruction guide carefully to understand how to use the product safely and effectively.

## General Safety Guidelines

- Always ensure that your reloading equipment is in good working condition before use.
- Keep the product out of reach of children and vulnerable individuals.
- Use the product only for its intended purpose as described in this guide.
- Regularly inspect the product for any signs of wear or damage.
- Report any unsafe products or accidents to the appropriate authorities.
- Check for recall updates on the EU's Safety Gate platform.

## Specific Safety Precautions for Use

- Before using the Primer Stop Switch, familiarize yourself with the Dillon XL650 and SL900 reloading systems.
- Ensure that the primer feed assembly is clear of obstructions before activating the switch.
- Do not attempt to adjust dies or clear jams while the primer indexing system is activated.
- When using the switch, avoid placing your fingers near moving parts to prevent injury.
- Always toggle the primer indexing system OFF when setting up cases without feeding primers.

## Instructions for Installation and Usage

### Installation

1. Ensure that the Dillon XL650 or SL900 press is unplugged and turned off.
2. Locate the area where the Primer Stop Switch will be installed.
3. Follow the manufacturer's instructions for attaching the switch securely to the press.
4. Ensure that the magnetattached ramp is properly positioned to allow for safe operation.

### Usage

1. To activate the Primer Stop Switch, toggle the switch to the ON position.
2. When you need to retract the indexing lever for adjustments or clearing jams, toggle the switch to the OFF position.
3. Confirm that the indexing lever has passed safely over the primer feed assembly before resuming normal operations.
4. After use, always return the switch to the OFF position when not in operation.

## Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic waste.
- Do not dispose of the product in regular household waste.
- Consider recycling the product if applicable.

## **Contact Information for Further Support**

For any questions or concerns regarding the use of this product, please refer to the manufacturer's support resources.