

Small Pin for Armanov Swage PRO | Dillon XL650 / XL750 - Milled Aluminium Station One Locator for Dillon XL650/XL750 (W - 13267)

Eliminate the weak link in your progressive reloading cycle. Station One dictates the alignment of your entire progressive run, yet factory components often flex under heavy use, leading to tilted cases and jammed indexing. The Armanov Station One Locator # is precision CNC-machined from premium high-grade aluminium, delivering industrial rigidity to ensure every cartridge enters the cycle with absolute geometric perfection.



Attributes

- Name: Milled Aluminium Station One Locator for Dillon XL650/XL750 (W - 13267)
- Manufacturer: ARMANOV
- Product no.: EU2018691
- Mfr. No.: ST1LAL-W
- Colour: Silver
- Delivery weight: 1kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 100mm

Table of Contents

- [Startpage](#)
- [English: Safety Instruction Guide for Small Pin for Armanov Swage PRO | Dillon XL650 / XL750](#)

Safety Instruction Guide for Small Pin for Armanov Swage PRO | Dillon XL650 / XL750

Introduction

Thank you for choosing the Small Pin for Armanov Swage PRO, designed specifically for the Dillon XL650 and XL750 reloading systems. This guide provides essential safety instructions to ensure safe and effective use of the product while complying with the EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Always read and understand the safety instructions before using the product.
- Ensure that the product is used only for its intended purpose as specified in this guide.
- Keep the product out of reach of children and vulnerable individuals.
- Inspect the product for any damage or wear before each use.
- Report any unsafe conditions or product defects to the appropriate authorities.

Specific Safety Precautions for Use

- **Hazard Identification:**
 - Improper installation or use may lead to malfunctions, resulting in injury or damage.
 - Ensure that the product is securely attached to avoid detachment during operation.
 - Be cautious of sharp edges during handling to prevent cuts or injuries.
- **Avoiding Hazards:**
 - Always wear appropriate personal protective equipment (PPE) such as safety glasses and gloves when using the product.
 - Do not exceed the manufacturer's recommended load limits.
 - Ensure that the work area is clean and free from obstructions before beginning installation or use.
- **AgeSpecific Warnings:**
 - This product is not intended for use by individuals under the age of 18.
 - Keep the product away from children and ensure that they do not have access to it.

Instructions for Installation and Usage

- **Installation:**
 1. Ensure that the Dillon XL650 or XL750 is turned off and unplugged before installation.
 2. Remove any existing components as per the manufacturer's instructions.
 3. Align the Small Pin with the designated slot on the Station One Locator.
 4. Securely fasten the pin, ensuring it is properly seated and does not move.
 5. Doublecheck the installation before use to ensure everything is secure.
- **Usage:**
 1. Begin your reloading process by following the standard operating procedures for the Dillon XL650 or XL750.
 2. Monitor the alignment of the cartridges throughout the reloading cycle.
 3. If you notice any irregularities such as tilted cases or jamming, stop the operation immediately and

- inspect the installation of the Small Pin.
4. Make adjustments as necessary and resume only when it is safe to do so.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in household waste.
- If the product is damaged or no longer usable, consider recycling options where available.

Contact Information for Further Support

For any inquiries regarding safety, installation, or product support, please consult your retailer or the manufacturer's website for contact details. Always ensure you have the product information available when seeking assistance.

Thank you for your attention to these safety instructions. Your safety is our priority!